

2018

Pine County Fair

Antique Class

1. **1964** and older, **NO** imperials or frame swaps. Please list year, make and model of car on entry form.
2. **NO WHINERS!** This is about putting on a show for the crowd.
3. Fresh cars only Friday night.
4. **NO** tucking quarter panels or trunk. **NO** folding the roof down on wagons.
5. Rust holes in floors may be patched. Up to 1/8" material
6. Factory body bolts may be replaced. 4 extra body bolts allowed inside car. 4"x4"x1/4" plates. Cross members must be in stock location. **NO** hump plates.
7. Front Bumper: May be replaced with shock type bumper or 1/4" square tube or round tube. Ends to remain open. Bumper skin must be welded or bolted on.
8. Frame, from spindles forward only, may be plated on any 2 sides with flat stock only. A-frames may be welded. **NO** welding on the frame behind the spindles. **NO** stuffing the frame, hood, trunk lid or body panels.
9. Lower engine cradles allowed. **NO** mid plates, **NO** DP, **NO** full cradles, **NO** welded motor mounts behind the carb.
10. Angle iron allowed on top of core support. Front clip can be tied to frame in 4 places in front of the spindles.
11. Hood must be open for inspection. Can secure hood in 8 places, only 2 threaded rod through the frame at the core support. (Up to 1" Rod).
12. 4 point floating cage or X brace and dash bar. Cage can not extend 12" behind the door post. Cage can have 2 vertical kickers to the floor only. (Not to the frame).
13. Radi barrel or water tanks are allowed. Water barrel **NO** larger than 2'x2'x2' and must be vented back and down through the floor. Radi barrel must be attached to the core support only. **NO** braces going into the trunk area.
14. Driver's door reinforcement may not extend more than 2" out from the body and more than 6" past the door seam.
15. Body: Doors may be patch welded shut. Up to 5"x5" patches 4 per door. 2 door models 6 patches on passenger door. **NO** seam welding.
16. Trunk: Lid may be chained, bolted or welded shut. Up to 8 places. 2 threaded rod can run through the frame. (Up to 1" rod). **NO** seam welding
17. Any 5 lug rearend allowed. Can convert to leaf springs from any coil spring car.